

BORE and DOWEL DETAILS



One of the corner joints **DBS** offers is Bore & Dowel construction. We use only high quality, state-of-the-art production equipment to produce this detail.

TECHNICAL ASPECTS:

- The dowels are 6mm x 30mm hardwood.
- The dowels are pre-inserted in the front and back of the drawer.
- The dowels are 32 mm center to center installed.
- The dowels are set 20 mm into the front and back of the drawer.
- The drawer sides are full length and the ends are drilled to accept the dowels.
- The top edges of the sides are 1/16" taller than the front and back of the drawer.
- Standard bottom construction is let in on four sides and includes hot melt on assembled boxes. Bottom mount construction is also available.
- We recommend using this construction with all types of plywood and pre-laminated materials.

SIZING:

	Minimum	Maximum	Measured to
Width	4"	49.99" Assembled	1/32"
		Open Unassembled	
Depth	4"	40" Assembled	1/4"
		Open Unassembled	
Height	1.75"	28" Let in bottoms	1/8"
	1.25"	28" Bottom mount bottoms	

RECOMMENDATIONS:

Dowel is considered a premium grade corner joint according to most regulatory agencies. It is especially advantageous for knock down applications due to the ease of assembly.

We recommend this corner joint for all types of cabinetry, office furniture and residential furniture.

Order from your **DBS** representative

www.dbsdrawers.com (714) 744-4247 • (800) 422-9881 or fax us at (714) 744-0650